

## LRD 2984

### WORK LIGHT SLIM WITH REVERSING FUNCTION

The range of Horpol work lights has been expanded with products in the SLIM version: LRD 2983, LRD 2984 with a reversing function and LRD 2985 with a magnetic assemble base and a cigarette lighter plug. The LRD 2984 SLIM with a reversing light is distinguished by the comfort of using the lamp and the optimal combination of technical parameters. By engaging reverse gear, the work lights automatically switch on a little darker to avoid illuminating vehicles behind. The housing itself is made of aluminum, facilitating heat dissipation. The tilted support allows you to change the angle of inclination of the lamp, and thus the light distribution. Like other Horpol work lights, also SLIM lamps are equipped with LED diodes. The field of work is illuminated by 6 LEDs with a cold color, pleasant to the eye during night work. LRD lamps are completely resistant to cracks and impacts, extremely durable in contact with dirt and moisture.

### DANE TECHNICZNE

|                           |                             |   |
|---------------------------|-----------------------------|---|
| Dispersed light           | Light group                 | LED quantity                                |
| yes                       | HOR 73                      | 6   |
| Light category            | Supply voltage              | Light colour                                |
| working light             | 12/24 V                     | white                                       |
| Power rating              | Operating temperature range | Cable                                       |
| 20 W/4 W                  | from -30°C to +50°C         | 3×0,75 mm <sup>2</sup> ; cable length 1,5 m |
| Connection method         | Side                        | Reversing light                             |
| screw-on                  | universal                   | yes   |
| Colour temperature        | Luminous flux               | LED light                                   |
| 6500 K                    | 1800 lm                     | yes   |
| Ingress protection rating |                             |   |
| IP 68                     |                             |   |

