

LZD 2840

REAR MULTIFUNCTION LIGHT CLEOMAX

Attractive and modern design, high-quality materials and implemented energy-efficient LED technology, which ensures very good lighting parameters at very low power consumption, are the special hallmarks of multifunction lamp **CLEOmax LZD 2840**. The lamp is fully hermetic (ingress protection rating IP 68), and the operating temperature range is from -30 degrees C to + 50 degrees C. Only branded diodes are used for production, ensuring excellent quality of products. The operation of the lamp **LZD 2840** is also guaranteed in a way that does not emit electromagnetic interference and is electromagnetic interference-resistant, which is confirmed by the EMC certificate. **CLEOmax** is universal in assembly, it can be installed both on the left and right side of the vehicle, vertically and horizontally. The lamp fulfills the following functions: position light with NEON effect, direction indicator, brake light, fog light and reflective device. This model is dedicated to various types of vehicles such as trailers, semi-trailers, tow trucks, agricultural machines and special vehicles.

DANE TECHNICZNE

| | | |
|-----------------------------|-----------------------------|--------------------------|
| Light group | LED quantity | Light category |
| HOR 114 | 42 | multifunction rear |
| Rear position light | Supply voltage | Reflecting device |
| yes | 12/24 V | yes |
| Operating temperature range | Cable | Side |
| from -30°C to +50°C | 5x0,5 mm2; cable length 1 m | universal |
| Fog light | Brake light | Rear direction indicator |
| yes | yes | yes |
| LED light | Ingress protection rating | |
| yes | IP 68 | |

OPIS

Power consumption at 12/24 V operating voltage: - NEON position light - 1,7 W/4; - direction indicator - 3,3/7,3 W; - brake light - 3,5/4,2 W; - fog light - 5,3/6 W.

