

## LZD 2789/B

### FRONT MULTIFUNCTION LIGHT CLEOFRONT, BOTTOM MOUNT VERSION

Attractive and modern design, compact sizes, high-quality materials and implemented energy-efficient LED technology, which ensures very good lighting parameters at very low power consumption, are the special hallmarks of multifunction lamp **CLEOfont LZD 2789/B - bottom mount version**. The lamp is fully hermetic (ingress protection rating IP 68), and the operating temperature range is from -30 degrees C to + 50 degrees C. Only branded diodes are used for production, and their number is 32 pcs. The operation of the lamp is also guaranteed in a way that does not emit electromagnetic interference and is electromagnetic interference-resistant, which is confirmed by the EMC certificate. **LZD 2789/B** is universal in assembly, it can be installed both on the left and right side of the vehicle. The lamp fulfills the following functions: front position light with **NEON effect** and front direction indicator. This model is dedicated to various types of vehicles such as agricultural and construction machinery, specialized vehicles, forklifts, quads, light electric and municipal vehicles.

### DANE TECHNICZNE

Light group	LED quantity	Light category
HOR 115F	32	multifunction front
Supply voltage	Operating temperature range	Cable
12/24 V	from -30°C to +50°C	3×0,5 mm <sup>2</sup> ; cable length 1 m
Side	Front position light	LED light
universal	yes	yes
Ingress protection rating	Front direction indicator	
IP 68	yes	

### OPIS

**Power consumption at 12 V operating voltage:** – front position light (1,6 W); – front direction indicator (4,1 W). **Power consumption at 24 V operating voltage:** – front position light (3,6 W); – front direction indicator (4,6 W).

