

LZD 2789/R2

FRONT MULTIFUNCTION LIGHT CLEOFRONT, TUBE MOUNT VERSION

Attractive and modern design, compact sizes, high-quality materials and implemented energy-efficient LED technology, which ensures very good lighting parameters at very low power consumption, are the special hallmarks of multifunction lamp **CLEOfont LZD 2789/R2**. The lamp is fully hermetic (ingress protection rating IP 68), and the operating temperature range is from -30 degrees C to + 50 degrees C. Only branded diodes are used for production, and their number is 32 pcs. The operation of the lamp is also guaranteed in a way that does not emit electromagnetic interference and is electromagnetic interference-resistant, which is confirmed by the EMC certificate. **LZD 2789/R2 of tube mount version ø20÷30 mm** is universal in assembly, it can be installed both on the left and right side of the vehicle, vertically and horizontally. The lamp fulfills the following functions: front position light with **NEON effect** and front direction indicator. This model is dedicated to various types of vehicles such as agricultural and construction machinery, specialized vehicles, forklifts, quads, light electric and municipal vehicles.

DANE TECHNICZNE

Light group	LED quantity	Light category
HOR 115F	32	multifunction front
Supply voltage	Operating temperature range	Cable
12/24 V	from -30°C to +50°C	3×0,5 mm ² ; cable length 1 m
Side	Front position light	LED light
universal	yes	yes
Ingress protection rating	Front direction indicator	
IP 68	yes	

OPIS

Power consumption at 12 V operating voltage: – front position light (1,6 W); – front direction indicator (4,1 W). **Power consumption at 24 V operating voltage:** – front position light (3,6 W); – front direction indicator (4,6 W).

