

LZD 3051/H101/AMP

SET OF MULTIFUNCTIONAL LAMP MAVIC WITH REFLECTIVE DEVICE, ELECTRICAL CONDUIT AND STALK MARKER LIGHT

The wide range of modern **MAVIC** multifunctional lamps has been enriched with practical sets **with 3-function stalk marker lights**. Set of lamps **LZD 3051/H101/AMP** (left) and **LZD 3052/H101/AMP** (right) **with reflective device** are designed for vans, truck tractors, tow trucks, larger specialized and agricultural vehicles. **The main advantages of the sets:** - Thanks to the **double Superseal socket** in the body of the multifunctional lamp, it is possible to easily connect an integrated stalk marker light and license plate lighting in the vehicle or a power supply harness for marker lamps. - The quick connector of the **Click&Ride system** allows for easy and convenient assembly and disassembly of the marker lamp, without the need to replace the entire set. In case of an impact on the stalk marker light, the connector will trigger a secure disengagement of the marker lamp, preventing harm to the multifunctional light. The set includes all necessary elements for affixing the marker lamp to the multifunctional lamp. - **MAVIC** lamp equipped with a conduit and an **AMP 7 PIN socket**. - Lamps of HOR 108A and HOR 101 groups have European approvals and electromagnetic compatibility certificate (**EMC**). - Lights are fully hermetic (**ingress protection rating IP 68**), and the operating temperature range is from **-30 degrees C to +50 degrees C**. - A **special protective lens coating** has been provided for MAVIC to ensure resistance to scratches and mechanical damage. - Universal operating voltage of **12 V** and **24 V**. Our offer includes also **MAVIC lights with retroreflective triangle** and marker lamp **LZD 3049/H101/AMP** (left), **LZD 3050/H101/AMP** (right).

DANE TECHNICZNE

| | | |
|-------------------|-----------------------------|--|
| LED quantity | Light category | Rear position light |
| 98 | multifunction rear | yes |
| Supply voltage | Front clearance light | Rear clearance light |
| 12/24 V | yes | yes |
| Reflecting device | Operating temperature range | Cable |
| yes | from -30°C to +50°C | 6x0,5 mm ² ; length 0,3 m, AMP 7 PIN, round |
| Side marker light | Side | Reversing light |
| yes | left | yes |
| Fog light | Brake light | Rear direction indicator |
| yes | yes | yes |
| Arm | LED light | Ingress protection rating |
| yes | yes | IP 68 |

OPIS

Lamp functions and power consumption at 12/24 V operating voltage: - NEON rear position light (2/4 W); - NEON brake light (10/10 W); - NEON direction indicator (4/13 W); - reversing light (2/4,5 W); - fog light (4/4 W); - reflective device (MAVIC); - stalk marker light (0,5/1 W).

