

## LD 2165/GRAPHITE

### MARKER LIGHT

**LD 2165/GRAPHITE** is a marker light on a flexible hanger, compact in size and with a wide range of applications. The symmetrical design provides **universal mounting options** (both on the right and left side of a vehicle). The light will work well in various types of vehicles such as: - trailers and car transporters; - camper vans and caravans; - minibuses and vans; - agricultural and construction machinery; - trucks; - special vehicles. The light from the **GRAPHITE** collection features a sleek, dark shade, combining modern design with functionality for excellent visibility. **LD 2165/GRAPHITE features:** - front position light (white light); - rear position light (red light); With a universal voltage of **12/24 V**, this light is characterised by low power consumption (**12 V - 1 W, 24 V - 2 W**). The light has been manufactured only with **branded LEDs**, which ensure a unique quality of illumination and add a visual appeal to the contour of a vehicle in motion. The high **IP 68** rating and the operating temperature range of **- 30 degrees C to + 50 degrees C** make it a top quality product. ***Make sure you stay safe on the road! Discover our [collection of GRAPHITE lights, a stylish solution for the automotive industry.](#)***

### DANE TECHNICZNE

|                           |                             |   |
|---------------------------|-----------------------------|---|
| Light group               | LED quantity                | Light category                              |
| HOR 83G                   | 4                           | marker                                      |
| Rear position light       | Supply voltage              | Light colour                                |
| yes                       | 12/24 V                     | white-red                                   |
| Power rating              | Operating temperature range | Cable                                       |
| 1/2 W                     | from -30°C to +50°C         | 2×0,75 mm <sup>2</sup> ; cable length 0,5 m |
| Side                      | Front position light        | LED light                                   |
| universal                 | yes                         | yes   |
| Ingress protection rating |                             |   |
| IP 68                     |                             |   |

