

## LD 676/GRAPHITE

### MARKER LIGHT

The **LD 676/GRAPHITE** marker light combines elegant design with high functionality. With its dark shade, the light follows modern trends in vehicle design while providing adequate visibility on the road. **Product features:** – **Side marker light.** The lamp emits **orange** light to enhance road safety by making your vehicle better visible in various conditions. – The light can be mounted either **on a straight rubber support** or **on a tube**, providing more flexibility to suit the user's needs. – **Number of LEDs.** Fitted with **4** high-efficiency **LEDs**, the lamp provides efficient lighting with minimal energy consumption. – **Universal supply voltage.** Operating at **12/24 V**, it is perfect for a variety of vehicle types. – **Low power rating.** With a power output of **0.6 W** (at 12 V) and **1.2 W** (at 24 V), the light is energy-efficient, a property that translates into longer life and less strain on the battery. – **High IP 68 rating.** The light is fully hermetic and resistant to mechanical damage. – **Wide operating temperature range from -30°C to +50°C.** Suitable for all weather conditions, the product will be a reliable choice all year round. ***Make sure you stay safe on the road! Discover our collection of [GRAPHITE lights](#), a stylish solution for the automotive industry.***

### DANE TECHNICZNE

|                             |  |                           |
|-----------------------------|--|---------------------------|
| Light group                 | LED quantity                                 | Light category            |
| HOR 65G                     | 4  | marker                    |
| Supply voltage              | Light colour                                 | Power rating              |
| 12/24 V                     | amber  | 0,6/1,2 W                 |
| Operating temperature range | Cable  | Side marker light         |
| from -30°C to +50°C         | 2×0,75 mm <sup>2</sup> ; cable length 0,25 m | yes                       |
| Side                        | LED light                                    | Ingress protection rating |
| universal                   | yes  | IP 68                     |

