

## LD 2622/GRAPHITE/5M

### STALK MARKER LIGHT

**LD 2622/GRAPHITE/5M** is an **orange and red** marker light on a short arm. The product is universal in terms of mounting options. It can be fitted on either the left or the right side of a vehicle. Designed for use from small trailers to trucks and semi-trailers. The light from the **GRAPHITE** collection features a sleek, dark shade, combining modern design with functionality for excellent visibility. Operating at a universal voltage of **12/24 V**, the light is characterised by low energy consumption. The **light** has been manufactured only with **branded LEDs**, which ensure a unique quality of illumination and add a visual appeal to the contour of a vehicle in motion. The high **IP 68** rating and the operating temperature range of **- 30 degrees C to + 50 degrees C** make it a top quality product. ***Make sure you stay safe on the road! Discover our [collection](#) of GRAPHITE lights, a stylish solution for the automotive industry.***

### DANE TECHNICZNE

|                           |                             |                                       |
|---------------------------|-----------------------------|---------------------------------------|
| Light group               | LED quantity                | Light category                        |
| HOR 102AD                 | 10                          | marker                                |
| Rear position light       | Supply voltage              | Light colour                          |
| yes                       | 12/24 V                     | amber-red                             |
| Power rating              | Operating temperature range | Cable                                 |
| 1,9/3,9 W                 | from -30°C to +50°C         | 2x0,75 mm <sup>2</sup> , length 2x5 m |
| Side                      | Arm                         | LED light                             |
| universal                 | yes                         | yes                                   |
| Ingress protection rating |                             |                                       |
| IP 68                     |                             |                                       |

