

## LZD 2790/R2

### REAR MULTIFUNCTION LIGHT CLEO, TUBE MOUNT VERSION

The rear multifunction light CLEO, side mount version **LZD 2790/R2** is a compact light with modern design, made of premium materials and with energy-saving **LED** technology, offering excellent light performance with very low power consumption. The **LZD 2790/R2** light is fully water and dust resistant (**IP 68**), enabling trouble-free use whatever the terrain and weather conditions. The **32 high-performance LEDs** deliver even and intense light, increasing **visibility** and **safety on the road**. The product meets electromagnetic compatibility (**EMC**) standards to eliminate the risk of interference that could affect other vehicle electrical equipment. The **LZD 2790/R2** light,  $\varnothing 20 \div 30$  mm tube mount version, is universal in terms of mounting options. It can be mounted both on the left and right side of a vehicle, vertically and horizontally. This mounting means that installation of the light is extremely simple and flexible, and the light can be adapted to suit different types of vehicles and machines. **With light functions:** - **NEON** rear position light; - rear direction indicator; - break light. This model will perform well in agricultural and construction machinery, specialised vehicles, forklifts, quads, light electric vehicles and municipal vehicles, to name but a few, where reliability and durability are key assets.

### DANE TECHNICZNE

|  |                |                             |
|--|----------------|-----------------------------|
| Light group                              | LED quantity   | Light category              |
| HOR 115N                                 | 32             | multifunction rear          |
| Rear position light                      | Supply voltage | Operating temperature range |
| yes                                      | 12/24 V        | from -30°C to +50°C         |
| Cable                                    | Side           | Brake light                 |
| 4x0,5 mm <sup>2</sup> ; cable length 1 m | universal      | yes                         |
| Rear direction indicator                 | LED light      | Ingress protection rating   |
| yes                                      | yes            | IP 68                       |

### OPIS

**Power consumption at 12 V operating voltage:** - rear position light (2 W) - rear direction indicator (1,7 W) - break light (2,7 W) **Power consumption at 24 V operating voltage:** - rear position light (4,2 W) - rear direction indicator (4 W) - break light (3 W) Our range includes also [CLEO rear multifunction lights](#) in bottom mount [LZD 2790/B](#) and side mount [LZD 2790/W2](#).

