

## LRD 2679/RED

### WORK LIGHT

**LRD 2679/RED work lamp - red light for special tasks.** The LRD 2679/RED lamp is a compact and efficient source of **diffused red light**, designed for operation in demanding conditions. With a power output of **3,6 W** and a **luminous flux of 100 lm**, it provides comfortable illumination of the work area without dazzling the operator or others nearby. Its **universal operating voltage (12/24 V)** and flexible mounting options allow for easy installation on various vehicles and machines. The durable housing and **IP 68 protection rating** ensure reliable performance even in extreme environments – mud, dust, rain, or snow pose no threat. The lamp meets **R10 (EMC)** standards, meaning it does not interfere with the vehicle's electronic systems. It can operate within a wide temperature range, making it a perfect all-season solution. The LRD 2679/RED lamp is ideal for service and road vehicles, where the red light effectively marks the working zone, enhancing safety in road traffic and during nighttime operations.

### DANE TECHNICZNE

Dispersed light	Wavelength of light	Light group
yes	628 nm	HOR 111
LED quantity	Light category	Supply voltage
15	working light	12/24 V
Light colour	Power rating	Operating temperature range
red	3,6 W	from -30°C to +50°C
Cable	Side	Luminous flux
2×0,75 mm <sup>2</sup> ; cable length 1,5 m	universal	100 lm
LED light	Ingress protection rating	
yes	IP 68	

